

LIX-203 Cast Iron Pipe Clamp

Material: Malleable Cast Iron


Finish: Electro Zinc-Plated/Zinc Rich Composite

Size Range: 1/2 through 2"

Side Screws With Plastic Washer

Plastic Plug Should Be Used For Fixing (Type 12)







Nominal Pipe Size		Max. Rec. Load		Rod Size (RS)	А		В		С		D	
IN	MM	IBS	KG	IN	ММ	IN	MM	IN	MM	IN	MM	IN
1/2"	15	180	81.7	3/8"	57.6	2 1/4	13.4	1/2	20	4/5	33.7	1 1/3
3/4"	20	180	81.7	3/8"	62.8	2 1/2	13.4	1/2	22.2	8/9	38.6	1 1/2
1"	25	180	81.7	3/8"	70.1	2 3/4	14.3	4/7	25.8	1	46.7	1 5/6
1-1/4"	32	180	81.7	3/8"	77.6	3	14.3	4/7	31.1	1 1/4	56.3	2 2/9
1-1/2"	40	180	81.7	3/8"	84.5	3 1/3	14.3	4/7	34.1	1 3/8	62.3	2 4/9
2"	50	180	81.7	3/8"	97.2	3 5/6	14.3	4/7	40.6	1 5/8	74.8	3
	1N 1/2" 3/4" 1" 1-1/4" 1-1/2"	Size IN MM 1/2" 15 3/4" 20 1" 25 1-1/4" 32 1-1/2" 40	Size Wax. Re IN MM IBS 1/2" 15 180 3/4" 20 180 1" 25 180 1-1/4" 32 180 1-1/2" 40 180	Size Max. Rec. Load IN MM IBS KG 1/2" 15 180 81.7 3/4" 20 180 81.7 1" 25 180 81.7 1-1/4" 32 180 81.7 1-1/2" 40 180 81.7	Size Max. Rec. Load (RS) IN MM IBS KG IN 1/2" 15 180 81.7 3/8" 3/4" 20 180 81.7 3/8" 1" 25 180 81.7 3/8" 1-1/4" 32 180 81.7 3/8" 1-1/2" 40 180 81.7 3/8"	Size Max. Rec. Load (RS) IN MM IBS KG IN MM 1/2" 15 180 81.7 3/8" 57.6 3/4" 20 180 81.7 3/8" 62.8 1" 25 180 81.7 3/8" 70.1 1-1/4" 32 180 81.7 3/8" 77.6 1-1/2" 40 180 81.7 3/8" 84.5	Size Max. Rec. Load (RS) IN MM IBS KG IN MM IN 1/2" 15 180 81.7 3/8" 57.6 2 1/4 3/4" 20 180 81.7 3/8" 62.8 2 1/2 1" 25 180 81.7 3/8" 70.1 2 3/4 1-1/4" 32 180 81.7 3/8" 77.6 3 1-1/2" 40 180 81.7 3/8" 84.5 3 1/3	Size Max. Rec. Load (RS) A B IN MM IBS KG IN MM IN MM 1/2" 15 180 81.7 3/8" 57.6 2 1/4 13.4 3/4" 20 180 81.7 3/8" 62.8 2 1/2 13.4 1" 25 180 81.7 3/8" 70.1 2 3/4 14.3 1-1/4" 32 180 81.7 3/8" 77.6 3 14.3 1-1/2" 40 180 81.7 3/8" 84.5 3 1/3 14.3	Size Max. Rec. Load (RS) A B IN MM IBS KG IN MM IN MM IN 1/2" 15 180 81.7 3/8" 57.6 2 1/4 13.4 1/2 3/4" 20 180 81.7 3/8" 62.8 2 1/2 13.4 1/2 1" 25 180 81.7 3/8" 70.1 2 3/4 14.3 4/7 1-1/4" 32 180 81.7 3/8" 77.6 3 14.3 4/7 1-1/2" 40 180 81.7 3/8" 84.5 3 1/3 14.3 4/7	Size Max. Rec. Load (RS) A B IN MM IBS KG IN MM IN MM IN MM 1/2" 15 180 81.7 3/8" 57.6 2 1/4 13.4 1/2 20 3/4" 20 180 81.7 3/8" 62.8 2 1/2 13.4 1/2 22.2 1" 25 180 81.7 3/8" 70.1 2 3/4 14.3 4/7 25.8 1-1/4" 32 180 81.7 3/8" 77.6 3 14.3 4/7 31.1 1-1/2" 40 180 81.7 3/8" 84.5 3 1/3 14.3 4/7 34.1	Size Max. Rec. Load (RS) B C IN MM IBS KG IN MM IN MM IN MM IN 1/2" 15 180 81.7 3/8" 57.6 2 1/4 13.4 1/2 20 4/5 3/4" 20 180 81.7 3/8" 62.8 2 1/2 13.4 1/2 22.2 8/9 1" 25 180 81.7 3/8" 70.1 2 3/4 14.3 4/7 25.8 1 1-1/4" 32 180 81.7 3/8" 77.6 3 14.3 4/7 31.1 1 1/4 1-1/2" 40 180 81.7 3/8" 84.5 3 1/3 14.3 4/7 34.1 1 3/8	Size Max. Rec. Load (RS) B C IN MM IBS KG IN MM IN MM IN MM IN MM 1/2" 15 180 81.7 3/8" 57.6 2 1/4 13.4 1/2 20 4/5 33.7 3/4" 20 180 81.7 3/8" 62.8 2 1/2 13.4 1/2 22.2 8/9 38.6 1" 25 180 81.7 3/8" 70.1 2 3/4 14.3 4/7 25.8 1 46.7 1-1/4" 32 180 81.7 3/8" 77.6 3 14.3 4/7 31.1 1 1/4 56.3 1-1/2" 40 180 81.7 3/8" 84.5 3 1/3 14.3 4/7 34.1 1 3/8 62.3

Measurements are subject to 5% tolerance

Due to continuous improvement, product specifications are subject to change without prior notice. Revised o



