

## U Strap Clamps For Rubber Support Insert

Application: Designed and recommended for the mounting of insulated or non-insulated pipes and can be used with rubber support inserts.

Size Range: 1/2" through 24"


Material: Carbon Steel

Finish: Standard Electro zinc plated/Zinc rich

Composite

Option-Hot dipped galvanized/Copper collar coating

Approvals Complies with Federal Specification A-A-11924 (type 26), WW-H-171E (type 26), MSS SP-89 and MSS SP-58 (type 26).



Installation with Rubber support Insert



	MM	MM	MM	MM	
1/2 × 1	68	120	95	25 × 3	M8
3/4 × 1	74	144	113	25 × 3	M8
1 × 1	81	151	119	25 × 3	M8
1 1/4 × 1	90	160	128	25 × 3	M8
1 1/2 × 1	96	166	132	25 × 3	M8
2 × 1	108	178	146	25 × 3	M8
2 1/2 × 1	121	191	159	38 × 3	M10
3 × 1	137	207	175	38 × 3	M10
3 1/2 × 1	149	219	187	38 × 3	M10
4 × 1	162	232	200	38 × 3	M10
5 × 1	189	259	227	38 × 3	M10
6 × 1	216	292	260	50 × 4.5	M10
3/4 × 2	124	194	162	25 × 3	M10
1 × 2	131	201	169	25 × 3	M10
1 1/4 × 2	140	210	178	25 × 3	M10
1 1/2 × 2	146	216	184	25 × 3	M10
2 × 2	158	228	196	25 × 3	M10
2 1/2 × 2	171	241	209	38 × 3	M10
3 × 2	187	257	225	38 × 3	M10
3 1/2 × 2	199	269	237	38 × 3	M10
4 × 2	212	282	250	38 × 3	M10
5 × 2	239	330	289	38 × 3	M12
6 × 2	266	357	316	50 × 4.5	M12
8 × 2	317	420	379	50 × 4.5	M18
10 × 2	371	463	422	50 × 4.5	M18
12 × 2	422	533	492	50 × 4.5	M18
14 × 2	454	545	503	50 × 4.5	M18
16 × 2	504	595	554	50 × 4.5	M18
18 × 2	555	646	605	50 × 4.5	M18
20 × 2	606	705	664	50 × 4.5	M18
24 × 2	707	815	767	50 × 6	