

Material: Carbon Steel
 Size Range: 1/2 Through 24
 Finish: Electro Galvanized/Zinc Rich Composite.
 M6 Side Screws With Two Pieces Of Gasket
 Designed And Recommended For The Mounting Of
 Insulated
 Dr Non-Insulated Pipes, And Can Be Used With Rubber
 Supports Inserts.
 Comply With Federal Specification WW171E And
 American
 Manufactures Standardization Society MSS SP-69 &
 SP58(Type 261



Nominal Pipe Size	Max. Rec. Load		Bolt Size (RS)	D		B		A		T		W	
IN	IBS	KG	MM	IN	MM	IN	MM	IN	MM	IN	MM	IN	MM
1/2"	550	249	M8	6/7	22	2	51	3	76	1/8	3	1	25
3/4"	550	249	M8	1 1/9	28	2 1/4	57	3 2/9	82	1/8	3	1	25
1"	550	249	M8	1 3/8	35	2 1/2	64	3 1/2	89	1/8	3	1	25
1-1/4"	550	249	M8	1 2/3	42	2 4/5	71	3 7/9	96	1/8	3	1	25
1-1/2"	550	249	M8	1 8/9	48	3	77	4	102	1/8	3	1	25
-	550	249	M8	2 1/8	54	3 1/4	83	4 1/4	108	1/8	3	1	25
2	650	295	M8	2 2/3	68	3 5/6	97	4 4/5	122	1/8	3	1	25
2-1/2	650	295	M8	3	74	4 2/5	112	5 2/3	144	1/8	3	1	25
-	650	295	M8	3 1/5	81	4 2/3	119	6	151	1/8	3	1	25
3	650	295	M8	3 1/2	90	5	128	6 2/7	160	1/8	3	1	25
3 1/2	650	295	M8	3 7/9	96	5 2/7	134	6 1/2	166	1/8	3	1	25
-	650	295	M8	4 1/4	108	5 3/4	146	7	178	1/8	3	1	25
4	650	295	M8	4 3/4	121	6 1/4	159	7 1/2	191	1/8	3	1 1/2	38
-	650	295	M10	4 7/8	124	6 3/8	162	7 2/3	194	1/8	3	1	25
-	650	295	M10	5 1/6	131	6 2/3	169	8	201	1/8	3	1	25
5	650	295	M10	5 2/5	137	6 8/9	175	8 1/7	207	1/8	3	1 1/2	38
-	650	295	M10	5 6/7	149	7 1/3	187	8 5/8	219	1/8	3	1 1/2	38
-	650	295	M10	5 1/2	140	7	178	8 1/4	210	1/8	3	1	25
-	650	295	M10	5 3/4	146	7 1/4	184	8 1/2	216	1/8	3	1	25
-	650	295	M10	6 2/9	158	7 5/7	196	9	228	1/8	3	1	25
6	650	295	M10	6 3/8	162	7 7/8	200	9 1/7	232	1/8	3	1 1/2	38
-	650	295	M10	7 4/9	189	9	227	10 1/5	259	1/8	3	1 1/2	38

Measurements are subject to 5% tolerance Que to continuous improvement, product specifications are subject to change without prior notice