


## Heavy Duty U-Strap With EPDM Rubber lining



Measurements are subject to 5% tolerance

\*Due to continuous improvement, product specifications are subject to change without prior notice.

Nominal Pipe Size	Max. Rec. Load		Bolt Size (RS)	D		B		A		T		W	
IN	IBS	KG	MM	IN	MM	IN	MM	IN	MM	IN	MM	IN	MM
-	650	295	M10	6 3/4	171	8 2/9	209	9 1/2	241	1/8	3	1 1/2	38
-	900	408	M10	7 1/3	187	8 6/7	225	10 1/8	257	1/8	3	1 1/2	38
-	900	408	M10	7 5/6	199	9 1/3	237	10 3/5	269	1/8	3	1 1/2	38
8	900	408	M10	8 1/2	216	10	254	11 1/4	286	1/6	4.5	2	50
-	900	408	M10	8 1/3	212	9 5/6	250	11 1/9	282	1/8	3	1 1/2	38
-	900	408	M12	9 2/5	239	11	277	12 1/6	309	1/8	3	1 1/2	38
10	1350	612	M12	10 1/2	266	12 4/9	316	14	357	1/6	4.5	2	50
12	1350	612	M18	12 1/2	317	14 4/9	367	16	408	1/6	4.5	2	50
14	1900	862	M18	14 3/5	371	16 4/7	421	18 1/5	462	1/6	4.5	2	50
16	1900	862	M18	16 3/5	422	18 4/7	472	20 1/5	513	1/6	4.5	2	50
18	1900	862	M18	17 7/8	454	19 5/6	504	21 1/2	545	1/6	4.5	2	50
20	1900	862	M18	19 5/6	504	21 4/5	554	23 3/7	595	1/6	4.5	2	50
-	1900	862	M18	21 6/7	555	23 5/6	605	25 3/7	646	1/6	4.5	2	50
24	1900	862	M18	23 6/7	606	25 5/6	656	27 4/9	697	1/6	4.5	2	50
-	2400	1089	M18	27 5/6	707	30 1/5	767	32	815	1/6	4.5	2	50

Maresia Carbon Steel

Size Range: 1/2" Through 24

Finish. Electro Galvanized/Zinc Rich Composite

MB Side Screws With Two Pieces Of Gasket

Designed And Recommended For The Mounting Of Insulated Or Non-Insulated Pipes.

And Can Be Used With Rubber Supports Inserts

Comply With Federal Specification WW-H-171E And American

Manufactures Standardization Society MSS SP-69 & SP58 (Type 26)