

Four Bolt Underground Pipe Clamp

FUNCTION: Designed for clamping the csalked joints of underground

A.W.WA. ductile iron water pipe lines to prevent separation of joints.


APPROVALS Complies with National Fire Protection Association Standard 24

for 4 thru 12 pipe.

MATERIAL Carbon steel

FINISH: Plain, Electro Galvanized, Zinc Rich Composite

Complies with MSS SP58&SP59 (Type Bi)



Pipe Size	Max. Pipe O.D.	B	C	D	Bolt Size E	Max. Test Pressure P.S.I.	Recom. Tie Rod Size	Force On Clamp (in lbs.)	Wt. Each (in lbs.)
3	3.96	13 3/8	9 3/8	1 1/4	5/8 × 3	3/4	250	4550	8.60
4	4.80	14 1/2	10 1/8	1 1/4	5/8 × 3	3/4	250	4550	9.38
6	6.90	17	12 5/8	1 1/4	5/8 × 3	3/4	250	9340	11.50
8	9.05	19 3/4	15 3/8	1 1/4	5/8 × 3 1/2	3/4	250	16080	20.54
10	11.10	22	17 1/8	1 1/4	3/4 × 3 1/2	3/4	250	24180	23.15
12	13.20	25 5/8	20 1/2	1 1/4	7/8 × 3 1/2	1	250	34230	35.85
14	15.30	28 1/4	23 1/8	1 3/4	7/8 × 4	1	120	22200	46.78
16	17.40	31 7/8	25 7/8	1 3/4	1 × 4	1 1/8	115	27760	70.53
18	19.50	36	29	1 3/4	1 1/4 × 4 1/2	1 1/4	100	23900	84.65
20	21.60	38 1/8	31 1/8	1 3/4	1 1/4 × 4 1/2	1 3/8	75	27500	98.65
24	25.80	44 1/8	36 1/8	1 3/4	1 1/2 × 5	1 1/2	50	26200	135.50

Mete Clamps masche comicted by means of Inmadefods and the met drawn light on the washers to passa light jot

"Measurements are subject to 5% erence *Doa mperdict speciicants are subject to change wetost pe