

## LIX-301 Adjustable Roller Hanger

Finish: Electro Galvanized/Zinc Rich Composite
Designed for Suspending Pipe Where Langitudinal
Movement and Vertical Adjustment is required
Comply with Federal Specification WW H 1716 and
American Mamfactures Standardization Society MSS SP-59 & SP-58 (Type 43)

Material: Steel with Cast Iron Roller





ominal Pipe	Dimensions (mm)							Max. Rec.Load	
Size —	A	В	С	D	Н	К	Bracket Size	IBS	KG
2"	10	35	122	64	41	57	3×25	150	68
2-1/2"	12	44	148	92	50	74	3×25	225	101
3"	12	44	161	94	56	81	6×32	310	140
3-1/2	12	45	180	110	65	88	6×32	390	176
4"	12	46	192	122	69	93	6×40	475	214
5"	12	50	233	152	88	114	6×50	685	308
6"	19	50	260	180	102	125	6×50	780	351
8"	22	50	326	230	131	152	10×65	780	351
10"	22	50	381	285	161	178	10×65	965	434
12"	22	55	440	335	192	208	12×65	965	434
14"	25	55	478	372	212	221	12×65	1200	540
16"	25	55	524	421	233	247	12×65	1400	630
18"	25	65	590	474	267	283	12×65	1400	630
20"	32	65	664	522	300	305	16×75	1600	720
24"	32	75	788	630	351	367	16×100	1800	810

Measurements are subject to 5% tolerance. Due to continuous improvement, product specifications are subject to change without prior notice.



